

Flow Product Configuration Form

PROCESS DETAILS				
Liquid Type	Select:	Please enter product series/number, mixture ratio, or other details below.		
Liquid Flow Rate	Units:	Nominal:	Maximum:	Minimum:
Liquid Temperature	Units:	Nominal:	Maximum:	Minimum:
Liquid Pressure	Units:	Operating:	Maximum:	
System Pipe/Tubing	Type:	Material:		
Connections to Flow Product	Inlet:	Outlet:		
Inner Diameter (ID)	Minimum ID of pipe/fitting orifice at inlet:			
FLOW PRODUCT REQUIREMENTS				
Plumbing Connections	Select:			
Flow Body Material	Select:			
Flow Sensor Output Format	Select:			
CONFIGURATION / CUSTOMIZATION OPTIONS				
Flow Switch (Relay Output)	Yes ▶ Trip-point value:	Default	Custom ▶ Flow rate:	Units:
Factory-Installed Fittings	Yes ▶ Fitting type or mfr. part no.:			
Factory-Installed Cable Conn.	Yes ▶ Connector type or mfr. part no.:			
Temperature Meas. Capability	Yes ▶ Temp. sensor output format:			
Pressure Meas. Capability	Yes ▶ Pressure sensor output format:			
Other Requirements/Requests				
CALIBRATION OPTIONS				
Flow Calibration	Yes ▶ Output value:		= Flow rate:	Units:
Viscosity Calibration	Yes ▶ Kinematic visc. (cSt):		Fluid temperature:	Units:
Temperature Calibration	Yes ▶ Calibration value (°C):			
Other Calibration Rqmts.				

NAME: _____ EMAIL: _____
 COMPANY: _____ PHONE: _____

Please send this completed form to Proteus Applications Support at tech@proteusind.com.



Proteus Industries Inc.
 340 Pioneer Way, Mountain View, CA 94041
 Tel: (650) 964-4163 Fax: (650) 965-0304
www.proteusind.com sales@proteusind.com

Information in this document was correct at the time of printing; however, specifications are subject to change as Proteus Industries' continuous improvement processes establish new capabilities.
 © Proteus Industries Inc. All rights reserved. All other company and product names may be trademarks of their respective companies.

MKT00128 Rev 002 03/2021